



Cameo™ Series Mobile Printers

For business on the go

Lightweight receipt printers keep your business moving

Receipt printing is quick and efficient with lightweight, versatile Cameo mobile printers. Weighing as little as 0.45kg, they are light, sleek and durable enough to carry and use anywhere. Easily clipped to a user's belt, Cameo printers simplify in-store customer order processing and payment via optional bi-directional MCRs (magnetic card readers) and smart card readers.

Wireless communication

Bluetooth™ wireless option is available to enable wireless connection with any Bluetooth-enabled device such as the Zebra Portable Radio (ZPR).



Reliability on demand™

Cameo™ Series



Meet the Cameo family

Leading-edge connectivity

- All Cameo printers support a wide variety of communication options, including connections via serial or wireless via IrDA or SRRF, available in 433MHz, 916MHz and 2.4GHz frequencies
- Integrated long-range radio for wireless LAN connectivity (Cameo 3SC™)

Lightweight and long-lasting

- Printers weigh as little as 0.45kg
- High-performance battery power lasts more than eight hours on a single charge

Rugged design

- High-impact Texin® plastic housing
- Withstand drops up to 1.8m

Point-of-transaction flexibility

- Kerb-side airport check-in and hire-car returns speed people on their way with handheld scanners and mobile receipt printers
- Shorter queues mean happier customers. Receipt printers with credit card readers are used for queue cutting in retail stores and fast food restaurants

Cameo 2™

Weighing just 0.45kg, the Cameo 2 is easy to wear and carry anywhere receipt printing is needed. The convenient magnetic card reader option (shown above) enables you to perform credit card transactions while staying mobile. The Cameo 2 is ideal for point-of-sale transactions, hospitality receipt printing and transportation ticket printing.

Maximum Print Area

Width: 48.3mm (1.9")
Length: 280mm (11")

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

76.2mm (3") per second

Memory

256K SRAM; 1MB Flash

Physical Characteristics

Width: 94mm (3.7")
Depth: 66mm (2.6")
Height: 167.6mm (6.6")
Weight (with battery): 0.45kg (1lb)

Media Specifications

Receipt media width:
25.4mm (1") to 53.3mm (2.1")

Cameo 2SC™/2 Plus™

The 0.45kg Cameo 2SC and 2 Plus are Zebra's smallest, low-cost mobile receipt and label printers. The Cameo 2SC offers MCR and/or SCR for customer processing venues. The Cameo 2 Plus with optional black bar sensor or linerless platen is ideal for shelf labelling, price marking, product and bin labelling and gaming/wager ticketing.

Maximum Print Area

Width: 48.3mm (1.9")
Length: 280mm (11")

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

76.2mm (3") per second

Memory

256K SRAM; 1MB Flash

Physical Characteristics

Width: 94mm (3.7")
Depth: 66mm (2.6")
Height: 167.6mm (6.6")
with MCR: same
with SCR: add 17.4mm (0.7")
Weight (with battery): 0.45kg (1lb)

Media Specifications

Receipt media width:
25.4mm (1") to 53.3mm (2.1")



Cameo 3™

The Cameo 3 at only 0.64kg may be lightweight but its rugged design enables it to adapt to the harshest environments and survive drops of up to 1.8 metres. This printer is ideal for car hire point-of-transaction processing, route accounting and package delivery, airline boarding pass printing, gaming/wager ticketing and parking tickets and violations.

Maximum Print Area

Width: 71.9mm (2.83")
Length: 254mm (10")

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

76.2mm (3") per second

Memory

256K SRAM; 1MB Flash

Physical Characteristics

Width: 117mm (4.6")
Depth: 66mm (2.6")
Height: 157.5mm (6.2")
Weight (with battery): 0.64kg (1.4lb)

Media Specifications

Receipt media width:
39mm (1.5") to 78.5mm (3.1")



Cameo 3SC™

Print customer receipts and tickets on the go with the compact 0.73kg Cameo 3SC. Offering MCR and/or SCR for customer processing venues, the Cameo 3SC is ideal for car rental point-of-transaction processing, retail sales receipts, airline boarding passes and gaming/lottery tickets.

Maximum Print Area

Width: 71.9mm (2.83")
Length: 260mm (10")

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

76.2mm (3") per second

Memory

256K SRAM; 1MB Flash

Physical Characteristics

Width: 117mm (4.6")
Depth: 66mm (2.6")
Height: 208mm (8.2")
Weight (with battery): 0.73kg (1.6lb)

Media Specifications

Receipt media width:
39mm (1.5") to 78.5mm (3.1")



Cameo PEP™

Intuitively designed, user-friendly and under 1kg in weight, the Cameo PEP (Portable Encoding Printer) makes processing transactions in high traffic areas quick and easy. It features an integrated magnetic card encoder (MCE) and can process ISO 7811-compliant credit cards, room keys, property passes and transportation tickets. The Cameo PEP is ideal for hotel guest check-in, gaming and casino property management, amusement park ride passes and entertainment venue access.

Maximum Print Area

Width: 71.9mm (2.83")
Length: 260mm (10")

Resolution

8 dots per mm (203dpi)

Maximum Print Speed

76.2mm (3") per second

Memory

256K SRAM; 1MB Flash

Physical Characteristics

Width: 135mm (5.3")
Depth: 68mm (2.7")
Height: 229mm (9")
Weight (with battery): 0.84kg (1.85lb)

Media Specifications

Receipt media width:
39mm (1.5") to 78.5mm (3.1")

Standard Features

- Print method: direct thermal
- High-impact Texin® polycarbonate/polyurethane blended plastic construction
- Smart battery management (monitors battery for longer life and performance)
- 1MB Flash memory
- Resident scalable fonts
- Adjustable stock width control for variable media roll sizes
- Paper-out sensor
- "Clam-shell" design for easy media loading
- Auto-temperature compensation and print contrast control
- External power on/off control from keypad, terminal or printer
- Windows® drivers (3.1, 95, 98, NT® v.3.51, NT v.4.0, 2000, CE)

Operating Characteristics

Environment

- Operating Temperature -15°C/5°F to 50°C/122°F
- Storage Environment -25°C/-13°F to 70°C/158°F
- Operating Humidity 10 to 90% non-condensing
- Storage Humidity 10 to 90% non-condensing

Electrical

- 8-pin RS232 connector serial port
- 1.6 a.h. NiMH
- Shock-mounted internal components

Communication Interface Capabilities

- RS-232 connector serial port; configurable baud rate 9,600-115,200, parity, data bits; software (XON/XOFF) or hardware (DTR/DSR) communication handshake protocols; error detection CRC protocol

Agency Approvals

- FCC Class B Part 15; CE compliance

Media Characteristics

Labels

Max. Roll Size

- 56mm (2.2") O.D. on a 19mm (0.75") I.D. core (48mm (1.9") for Cameo 2 Plus™)

Thickness (receipt)

- 3.2mm to 5.0mm

Media Types

- Continuous receipt (Cameo 2™ and Cameo 3™), black mark (Cameo 2 Plus)

For optimum print quality and printer performance, use genuine Zebra supplies.

Fonts/Graphics/Symbologies

Character Fonts/Sets

- 25 types, downloadable, scalable fonts

Graphic Features

- Supports user-defined fonts and graphics – including custom logos

Bar Code Symbologies

- Code 39, Code 93, Code 128, NW-7, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, EAN-8, EAN-18, MSI/Plessey, Postnet, UCC/EAN-128
- 2-Dimensional: PDF-417, Maxi Code

Options and Accessories

- Bluetooth™ connectivity
- Zebra Portable Radio (ZPR) for Symbol® SPT 1700/1800 & PPT 2700/2800 handheld devices
- Wireless short-range RF communication
- Wireless I/R communication
- Environmental case for increased printer protection from harsh environments
- Soft case, shoulder strap or belt clip
- UCN72 Fast Battery Chargers
- UCN74 Quad Battery Chargers
- Label Vista™ software for receipt and label design and font creation



Communicate wirelessly with Cameo™ printers using a Symbol terminal and Zebra Portable Radio (ZPR)

For further information on these products, please visit the Zebra web site at: www.zebra.com



Zebra Bar Code Products

European Headquarters

Zebra House, The Valley Centre
Gordon Road, High Wycombe
Buckinghamshire HP13 6EQ
United Kingdom

Tel: +44 (0)1494 472872
Fax: +44 (0)1494 450103

Regional Sales Office

Birkenwaldstr. 38
D-63179 Obertshausen
Germany

Tel: +49 (0)6104 70990
Fax: +49 (0)6104 709922

Regional Sales Office

50 rue Marcel Dassault
F-92100 Boulogne-Billancourt
France

Tel: +33 (0)1 55 20 93 93
Fax: +33 (0)1 55 20 93 99

International Headquarters

333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109
USA

Tel: +1 (847) 634-6700 or (800) 423-0442
Fax: +1 (847) 913-8766

Other Locations

United States: California, Florida, Rhode Island, Wisconsin

Europe: Denmark, Italy

Asia-Pacific: Australia, China, Japan, Singapore, South Korea

Middle East: Dubai

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.

